



Disposal Systems Drip Irrigation (Accessories)

PDS-PR-75-LF, PDS-PR-100-MF, PDS-125-HF

Features

- Preset to regulate pressure to the dripfield
- Required when using non-pressure compensating tubing
- Installed in-line on the supply manifold
- 3/4", 1" and 1 1/4" threaded inlets

Performance:

	Outlet Pressure	Flow Range
PDS-PR-75-LF	20 psi	1/10 - 8 gpm
PDS-PR-100-MF	20 psi	2 - 20 gpm
PDS-PR-125-HF	20 psi	10 - 32 gpm



Materials

Body

- Pressure Regulator
- High impact engineering grade thermoplastics
- Fixed stainless steel compression spring enclosed in a separate chamber

Warranty for Defects in Material and Workmanship

- Pressure Regulator - 1 Year

PDS-PG-60

Features

- 1/4" NPT lower mount
- Included in all drip management systems
- Allows for easy monitoring and setting of correct system pressure



Warranty for Defects in Material and Workmanship

- Pressure Gauge - 1 Year



P.O. Box 1520, Crestwood, Ky, 40014

Copyright 2006, Quanics Incorporated, All rights reserved

Product(s) covered by one or more U.S. and/or International patents. Other U.S. and International patents may be pending.